

V Series

Vehicle Tracker Specification



The V series tracker devices are ideally for vehicle , trailer tracking and remote monitoring and command control , supporting by ACC ignition , relay control and multiple GPIOs for data telematics . Integrates global connectivity by cellular network 2G,4G Cat.1 , NB-IoT and Cat.M1 without data plan contract .

The V series tracker devices have integrated multiple sensors for monitoring of movement , vibration , tampering , delay ,overspeed and geofence . Indoor and outdoor positioning supported by WIFI ,LBS and GPS ,GLONASS ,GALILEO and BEI-DOU . Short range wireless BLE [Bluetooth Low Energy] is flexible for easy configuration , pair with external BLE sensors or accessories , which makes V series tracker device working as BLE gateway .

Firmware over the air OTA is always important for after sale maintainece .The insight platform view location and condition data of your shipments in real time to ensure on time and in full delivery , specify the constraints relevant to your shipments and receive notifications when issues arise and create detailed reports to share with customers and analyze your data to identify improvement opportunities.



Key Benefits

- ◆ Integrate GNSS, Wi-Fi, LBS Multi-positioning technology, can quickly and accurately locate the vehicle, and support Bluetooth positioning indoors.
- ◆ Worldwide LTE CAT.1/CAT.M/, NBIOT and GSM/GPRS/EDGE coverage.
- ◆ Integrate multiple sensors to realize Unplug detection, Towing detection, Crash detection, Vibration detection.
- ◆ Support multiple peripheral interfaces, Digital input/output, RS485/TTL, etc. Digital input can be used for ignition (ACC), door or alarm button status monitoring. The digital output can be used to remotely control engine to turn off.
- ◆ The visualized cloud platform supports the full-scene status monitoring of vehicles and goods. At the same time, it also supports FOTA.



CAT.1/ CAT.M/
GSM/ NBIOT



Multi-constellation
GNSS



Wi-Fi 2.4G



Bluetooth 5.0



Multiple sensors



Speeding alarm



Remotely control
engine to turn off



Cloud-Platform
Service



Firmware Upgrade
OTA

V Series

Vehicle Tracker Specification



Variant for the Global

VT001-M-GL (Cat M1):

LTE FDD: B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25/B26*/B27/B28/B66/B71/B85

GSM: 850/900/1800/1900MHz

VT001-L-GL* (Cat 1):

LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28

GSM: 850/900/1800/1900MHz

VT001-G-GL(GSM only):

GSM: 850/900/1800/1900MHz

Variant for China/India

VT001-L-CN (Cat 1):

LTE FDD: B1/B3/B5/B8

LTE TDD: B34/B38/B39/B40/B41

GSM: 900/1800MHz

Variant for EMEA

VT001-L-EM (Cat 1):

LTE FDD: B1/B3/B5/B7/B8/B20/B28

GSM: 850/900/1800/1900MHz

Variant for Latin America

VT001-L-LA (Cat 1):

LTE FDD: B2/B3/B4/B5/B7/B8/B28/B66

GSM: 850/900/1800/1900MHz

Variant for North America

VT001-L-NA* (Cat 1):

LTE FDD: B2/B4/B5/B12/B13/B25/B26

VT001-M-NA (Cat M1):

LTE FDD: B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25/B26*/B27/B28/B66/B71/B85

Data

LTE (Cat 1):

LTE FDD: Max 10Mbps (DL)/Max 5Mbps (UL)

LTE TDD: Max 8.96Mbps (DL)/Max 3.1Mbps (UL)

LTE (Cat M):

LTE FDD: Max 588Kbps (DL)/Max 1119Kbps (UL)

GSM:

GPRS: Max 107Kbps (DL)/Max 85.6Kbps (UL)

EDGE: Max 296Kbps (DL)/Max 236.8Kbps (UL)

Command Set: Track protocol command

Transmit protocol: TCP, UDP, SMS

Working modes: Power saving mode for long standby time
Continuous mode for emergency tracking

Scheduled Timing Report:

Report position and status at preset time intervals

Wakeup Report: Report when the device wakes up

Geo-fences*: Support up to 5 internal geo-fence regions

Low Power Alarm: Alarm when internal battery is low

Motion Detection: Motion detection based on internal 3-axis accelerometer

Reporting Frequency Adjustment: The device will increase the position reporting frequency when it turns a corner

Hardware Features

USB: × 1, Micro

UART: × 1, RS485*, RS232*, 1-Wire*

(U)SIM Interface: × 1, 1.8V/3V, Nano SIM card

Cellular Antenna: internal

GNSS Antenna: internal, GPS/GLONASS/BeiDou

LED: × 3, System Light, Network Light, GNSS Light

WLAN: 2.4G (VT001-G no support)

Bluetooth: 5.0 (VT001-G no support)

Battery Capacity: 90mA (lithium polymer battery, optional)

GNSS Features

Horizontal Position Accuracy: Autonomous: <2.5m CEP

Velocity Accuracy: Without Aid: <0.1m/s

Acceleration Accuracy: Without Aid: <0.1m/s²

Reacquisition Time: <1s

TTFF @-130dBm with EASY™:

Cold Start: <15s; Warm Start: <5s; Hot Start: <1s

TTFF @-130dBm without EASY™:

Cold Start: <35s; Warm Start: <30s; Hot Start: <1s

General Features

Supply Voltage: 9V~ 40V (9V~ 100V optional)

Stand-by Current: ≤10mA

Operating Temperature: -20°C ~ +70°C

Dimensions: 82mm × 40mm × 18mm

Weight: Approx. 54g (VT001-G), 59g (VT001-M), 58g (VT001-L)

Firmware Upgrade: USB interface, OTA

Data Encryption*: TEA, AES or RSA (optional)

Power consumption: <10mA sleep mode@All variants

<1mA deep sleep mode@VT001-L/VT001-M variants

* Under Development

Electrical Characteristics

VT001-L/VT001-M:

- Supply Voltage:
Supply voltage (VCC): 9V~ 40V (9V~ 100V optional)
- Digital Output (open Drain)
Drain current (DO1-Digital Output OFF):
 $\leq 100\mu\text{A}$ (Default use for RELAY control)
Drain current (DO2-Digital Output OFF):
 $\leq 100\mu\text{A}$ (Can be used for normal output DO)
Drain current (DO1/DO2-Digital Output ON): $\leq 200\text{mA}$
- Digital Input
Input resistance (DI1) :
 $\geq 370\text{K}\Omega$ (Positive trigger input for ACC)
Input voltage (ACC): $\leq \text{VCC}$
Input voltage threshold (ACC) : $\geq 7\text{V}$
- Configurable Input:
Input resistance (DI1/AI1): $\geq 3\text{M}\Omega$ (Used for DI/AI)
Digital Input voltage (DI1):
 $\leq \text{VCC}$ (Negative trigger input for normal use)
Digital input voltage threshold (DI1): $\leq 0.2\text{V}$
Analog Input voltage (AI1): $\leq 16\text{V}$

VT001-G:

- Supply Voltage: 9V~ 40V (9V~ 100V optional)
- Digital Output (open Drain)
Drain current (DO1-Digital Output OFF):
 $\leq 100\mu\text{A}$ (Default use for RELAY control)
Drain current (DO1-Digital Output ON): $\leq 200\text{mA}$
- Digital Input
Input resistance (DI1) :
 $\geq 370\text{K}\Omega$ (Positive trigger input for ACC)
Input voltage (DI1): $\leq \text{VCC}$
Input voltage threshold (ACC) : $\geq 7\text{V}$

Interface Features

VT001-L/VT001-M:

VCC GND DI for Ign; DO for RELAY; DO; DI/AI (6 wires)

VT001-G:

VCC GND DI for Ign; DO for RELAY(4 wires)

Buffer Storage

VT001-L: 34000 message

VT001-M: 60000 message

VT001-G: 11000 message